

## HPT SERIES

### HYDROPNEUMATIC PRESSURIZED TANK



VERTICAL



HORIZONTAL (PUMP BASE)



INLINE

**Hydrosphere Hydropneumatic Pressurized Tanks** are an ideal product for well applications and for applications where you want to minimize pump start-ups every time you use water. When the pump fills the tank with water, the air above the diaphragm is compressed and the increased pressure inside the tank causes the pump to shut-off. Minimized pump starts and stops prevent motor damage due to excessive cycling of the pump, creates more consistent water pressure and provides savings through reduced energy use.

**Hydrosphere Hydropneumatic Pressurized Tanks** are constructed using high strength cold rolled carbon steel for added strength and painted with triple grade enamel making them extremely durable in outdoor applications.

**Hydrosphere Hydropneumatic Pressurized Tanks** come with stainless steel 304 NPT connections, offer a heavy-duty butyl rubber diaphragm and provide you with the peace of mind of an FDA grade polypropylene liner. This coupled with its 5-year warranty and durable design makes them the logical choice for industry professionals because of their cost to benefit ratio.

MJB 12/12/17





# HPT SERIES

## HYDROPNEUMATIC PRESSURIZED TANK

| INLINE MODELS  |                       |                              |                         |                       |                       |                                 |
|----------------|-----------------------|------------------------------|-------------------------|-----------------------|-----------------------|---------------------------------|
| Model Number   | Tank Volume (gal / L) | Maximum Acceptance (gal / L) | DIMENSIONS              |                       |                       | SHIPPING Tank Weight (lbs / kg) |
|                |                       |                              | Tank Diameter (in / cm) | Tank Height (in / cm) | Tank Connection (NPT) |                                 |
| HPT-305I-B10   | 0.5 gal / 3 L         | 0.25 gal / 0.95 L            | 5.1" / 13 cm            | 8.5" / 21.5 cm        | 1"                    | 1.2 lbs / 0.5 kg                |
| HPT-82I -B10   | 2 gal / 8 L           | 0.9 gal / 3.4 L              | 8" / 20.3 cm            | 11.4" / 29 cm         | 1"                    | 2.5 lbs / 1.1 kg                |
| HPT-1232I -B10 | 3.2 gal / 12 L        | 1.6 gal / 6.05 L             | 9.1" / 23 cm            | 15.4" / 39 cm         | 1"                    | 3.2 lbs / 1.4 kg                |
| HPT-1845I -B10 | 4.5 gal / 18 L        | 2.5 gal / 9.5 L              | 11" / 28 cm             | 15.4" / 39 cm         | 1"                    | 3.7 lbs / 1.7 kg                |
| HPT-246I -B10  | 6 gal / 24 L          | 3 gal / 11.4 L               | 11.6" / 29.5 cm         | 16.3" / 41.5 cm       | 1"                    | 4.6 lbs / 2.1 kg                |
| HPT-3810I -B10 | 10 gal / 38 L         | 5.2 gal / 19.7 L             | 11.6" / 29.5 cm         | 21.7" / 55 cm         | 1"                    | 6.4 lbs / 2.9 kg                |

| VERTICAL MODELS |                       |                              |                         |                       |                       |                                 |
|-----------------|-----------------------|------------------------------|-------------------------|-----------------------|-----------------------|---------------------------------|
| Model Number    | Tank Volume (gal / L) | Maximum Acceptance (gal / L) | DIMENSIONS              |                       |                       | SHIPPING Tank Weight (lbs / kg) |
|                 |                       |                              | Tank Diameter (in / cm) | Tank Height (in / cm) | Tank Connection (NPT) |                                 |
| HPT-5814V-B10   | 14 gal / 58 L         | 11.3 gal / 42.8 L            | 15" / 38.1 cm           | 23.6" / 66 cm         | 1"                    | 9.7 lbs / 4.4 kg                |
| HPT-8020V-B10   | 20 gal / 80 L         | 13 gal / 49.2 L              | 15" / 38.1 cm           | 30.7" / 78 cm         | 1"                    | 13 lbs / 5.9 kg                 |
| HPT-10025V-B10  | 28 gal / 100 L        | 15 gal / 56.8 L              | 15" / 38.1 cm           | 39.2" / 99.5 cm       | 1"                    | 15.5 lbs / 7 kg                 |
| HPT-12032V-B10  | 32 gal / 120 L        | 32 gal / 121 L               | 15" / 38.1 cm           | 44" / 112 cm          | 1"                    | 19.2 lbs / 8.7 kg               |
| HPT-13034V-B114 | 34 gal / 130 L        | 22.5 gal / 85 L              | 22" / 55.9 cm           | 29.5" / 75 cm         | 1 1/4"                | 22 lbs / 10 kg                  |
| HPT-16044V-B114 | 44 gal / 160 L        | 30 gal / 113.6 L             | 22" / 55.9 cm           | 36" / 91.5 cm         | 1 1/4"                | 25.5 lbs / 11.6 kg              |
| HPT-23562V-B114 | 62 gal / 235 L        | 35.2 gal / 133 L             | 22" / 55.9 cm           | 45.7" / 116 cm        | 1 1/4"                | 36.5 lbs / 16.5 kg              |
| HPT-30582V-B114 | 82 gal / 305 L        | 44 gal / 166.5 L             | 22" / 55.9 cm           | 57.1" / 145 cm        | 1 1/4"                | 46.8 lbs / 16.6 kg              |

| HORIZONTAL MODELS (PUMP BASE MODELS) |                       |                              |                         |                       |                       |                                 |
|--------------------------------------|-----------------------|------------------------------|-------------------------|-----------------------|-----------------------|---------------------------------|
| Model Number                         | Tank Volume (gal / L) | Maximum Acceptance (gal / L) | DIMENSIONS              |                       |                       | SHIPPING Tank Weight (lbs / kg) |
|                                      |                       |                              | Tank Diameter (in / cm) | Tank Height (in / cm) | Tank Connection (NPT) |                                 |
| HPT-1845H-B10                        | 4.5 gal / 18 L        | 2.5 gal / 9.5 L              | 11" / 28 cm             | 12" / 30 cm           | 1"                    | 5 lbs / 2.3 kg                  |
| HPT-246H-B10                         | 6 gal / 24 L          | 3 gal / 11.4 L               | 11.6" / 29.5 cm         | 12.6" / 32 cm         | 1"                    | 6 lbs / 2.7 kg                  |
| HPT-3810H-B10                        | 10 gal / 38 L         | 5.2 gal / 19.7 L             | 11.6" / 29.5 cm         | 12.6" / 32 cm         | 1"                    | 7.8 lbs / 3.5 kg                |
| HPT-5814H-B10                        | 14 gal / 58 L         | 11.3 gal / 42.8 L            | 15" / 38.1 cm           | 17" / 42.5 cm         | 1"                    | 11.7 lbs / 5.3 kg               |
| HPT-8020H-B10                        | 20 gal / 80 L         | 13 gal / 49.2 L              | 15" / 38.1 cm           | 17" / 42.5 cm         | 1"                    | 15 lbs / 6.8 kg                 |



### PUMP SPECIFICATIONS

- FACTORY PRE-CHARGE: 30 PSI ( 2 BAR)
- MAX. WORKING TEMP: 200 °F ( 93 °C)
- MAX. WORKING PRESSURE: 150 PSI ( 10 BAR)

### MATERIALS OF CONSTRUCTION

- SHELL: Cold Rolled Carbon Steel
- COATING: Triple Grade Enamel
- LINER: FDA GRADE Polypropylene
- DIAPHRAGM: Heavy-Duty Butyl Rubber
- CONNECTIONS: 304 Stainless Steel

### WARRANTY

MANUFACTURER WARRANTY: 5 year Limited Warranty

### WARNINGS



**WARNING: BEFORE INSTALLATION, READ CAREFULLY THE PRODUCT INSTALLATION AND OPERATION INSTRUCTIONS MANUAL. FAILURE TO FOLLOW THE INSTRUCTIONS MAY RESULT IN SERIOUS OR FATAL INJURY AND/OR PROPERTY DAMAGE. FAILURE TO FOLLOW THE INSTRUCTIONS WILL VOID THE PRODUCT WARRANTY.**



**WARNING: EXPLOSION HAZARD! FAILURE TO FOLLOW THE INSTRUCTIONS IN THE PRODUCT MANUAL CAN CAUSE A RUPTURE OR EXPLOSION, POSSIBLY CAUSING FATAL OR SERIOUS INJURY, LEAKING, FLOODING AND/OR PROPERTY DAMAGE.**



**WARNING: THIS STORAGE TANK IS DESIGNED FOR OPERATION IN COLD WELL SYSTEMS AND LIMITED TO A WORKING PRESSURE OF NO GREATER THAN 125PSI. INSPECT TANK REGULARLY. IF SIGNS OF CORROSION ARE PRESENT, REMOVE TANK FROM OPERATION IMMEDIATELY.**

*Hydrosphere will not be held responsible for damage deriving from improper use of the Hydropneumatic Pressurized Tanks.*

MJB 12/12/17

WARNING: Do not use with water that is micro-biologically unsafe or of unknown quality without adequate disinfection before or after the system.

Distributed by:

**HYDROSPHERE TECHNOLOGIES, LLC™**

[www.hydrospheretech.com](http://www.hydrospheretech.com)